

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Release spray TRS

UFI: PEC5-7NYF-4DSQ-RJ44

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Release spray

1.3. Details of the supplier of the safety data sheet

Company name:	Suter Kunststoffe AG	
Street:	Aefligenstrasse 3	
Place:	CH-3312 Fraubrunnen	
Telephone:	+41 (0)31 763 60 60	Telefax: +41 (0)31 763 60 61
e-mail:	info@swiss-composite.ch	
Internet:	www.swiss-composite.ch	
Responsible Departement:	Sales Team	

1.4. Emergency telephone number:Tox Info Suisse 145
from abroad +41 44 251 51 51**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Aerosol 1; H222-H229
Skin Irrit. 2; H315
STOT SE 3; H336
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane
Kohlenwasserstoffe, C7-C9, n-Alkane, Isoalkane, Cycloalkane
Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, Cycloalkane, <5% n-Hexan
Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten**Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.



Safety Data Sheet

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 2 of 18

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P501 Inhalt/Behälter gemäß Sondervorschrift 327 ADR der Problemabfallentsorgung zuführen.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Adverse physicochemical effects:

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

The accumulation in lowlying or closed rooms can cause increased danger of fire and explosion.

Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

The product will be applied by spraying.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

In use may form flammable/explosive vapour-air mixture.

Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming.

The product does have a sealed spraying device.

Caution! Container under pressure.

Possible adverse effects on humans and possible symptoms:

See section 11 for toxicological information.

Possible adverse effects on the environment:

See section 12 for environmental information.

Other adverse effects:

Rapid evaporation of the liquid can cause frostbite.

Result of the determination of PBT/vPvB properties:

See under section 12.5 - Results of PBT and vPvB assessment.

Endocrine disrupting properties:

This product does not contain any substance that exhibits endocrine disrupting properties towards humans, as no ingredient meets the criteria.

This product does not contain any substance that exhibits endocrine disrupting properties towards non-target organisms, as no ingredient fulfils the criteria.

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 3 of 18

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Aerosol: Active substances with propane/butane as propellant gas.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			30 - < 35 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
106-97-8	butane			30 - < 35 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
74-98-6	propane			10 - < 15 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes			5 - < 10 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
64742-49-0	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			1 - < 5 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
78-92-2	butan-2-ol			1 - < 5 %
	201-158-5	603-127-00-5	01-2119475146-36	
	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3, STOT SE 3; H226 H319 H335 H336			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	30 - < 35 %
		inhalation: LC50 = 23,3 mg/l (vapours); dermal: LD50 = > 2800 mg/kg; oral: LD50 = 5840 mg/kg	
74-98-6	200-827-9	propane	10 - < 15 %
		inhalation: LC50 = 800000 ppm (gases)	
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% n-hexane	5 - < 10 %
		inhalation: LC50 = 25,2 mg/l (vapours); dermal: LD50 = 2800 - 3100 mg/kg	
64742-49-0	920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes	5 - < 10 %
		inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 mg/kg; oral: LD50 = > 5840 mg/kg	
64742-49-0	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	1 - < 5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
78-92-2	201-158-5	butan-2-ol	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 2054 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Put victim at rest, cover with a blanket and keep warm. Do not leave affected person unattended. Move a vomiting patient lying on his back into a stable position on his side. If breathing is irregular or stopped, administer artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Self-protection of the first aider : Personal protection equipment: see section 8 First Aid.

Notes to physician: No special measures are necessary.

After inhalation

Remove victim out of the danger area. Provide fresh air. In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks.) Call a physician immediately. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label.

After contact with skin

Wash immediately with: water and soap. Rub greasy ointment into the skin.

Do not wash with: Solvents/Thinner

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Do NOT induce vomiting. Give nothing to eat or drink. Never give anything by mouth to an unconscious person or a person with cramps. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Cough, Dyspnoea , Cyanosis (blue coloured blood), Acidosis, Depression of central nervous system, Headache, Nausea, Dizziness, Dizziness, Inebriation, Unconsciousness.



Safety Data Sheet

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 5 of 18

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Regulation of the blood circulation, possible shock treatment.
Where appropriate artificial ventilation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Fire rating: B (Fires of liquids or liquid turning substances).

Unsuitable extinguishing media

Full water jet, Water spray jet

5.2. Special hazards arising from the substance or mixture

Gases emitted by burning organic materials must always be classified as respiratory poisons. Burning produces heavy smoke.

Hazardous combustion products:

Carbon monoxide Carbon dioxide (CO₂), Hydrocarbons, Pyrolysis products, toxic.

5.3. Advice for firefighters

Usual measures for fire prevention. Co-ordinate fire-fighting measures to the fire surroundings. In case of fire and/or explosion do not breathe fumes. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. Beware of reignition. Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. No sensitizing effect known.

Additional information

Special protective equipment for firefighters Wear a self-contained breathing apparatus and chemical protective clothing. DIN-/EN-Norms 469

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Avoid contact with skin, eyes, and clothing. Do not breathe vapour/aerosol. Remove all sources of ignition. Move persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Provide adequate ventilation.

For non-emergency personnel Use personal protection equipment.

For emergency responders: Use personal protection equipment. Use personal protection equipment.

For non-emergency personnel

Use personal protective equipment. The personal protective equipment must be adapted to the situation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Ensure waste is collected and contained. Suppress gases/vapours/mists with water spray jet. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Eliminate leaks if safe to do so. Remove container from the discharge area. Prevent expansion over a wide area (e.g. by containment or oil booms). Remove from the water surface (e.g. skim or vacuum). Cover the



Safety Data Sheet

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 6 of 18

sewage system.

For cleaning up

Clean-up methods for large quantities of spilled material: Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders). Shovel up and place in suitable containers for disposal. If large quantities of spilled material cannot be contained, the local authorities should be notified. should be notified. Clean-up methods for small quantities of spilled material: Clean up spilled quantities immediately. Wipe up with absorbent material (e.g. cloth, fleece). Collect in suitable, closed containers and take for disposal. Clean contaminated surfaces thoroughly. Recommended cleaning agents: Clean with detergents. Avoid solvents. Retain and dispose of contaminated wash water. Ensure that all waste water is collected and treated by a sewage treatment plant. Ventilate the affected area.

Other information

Suitable material to pick up: Sand Diatomaceous earth Universal binder Absorbent material, organic

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Measures to prevent aerosol and dust generation

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists, Eye contact, skin contact.

Technical ventilation of workplace. Vapours are heavier than air. Provide room air exhaust at ground level.

During filling, metering and sampling should be used if possible: Splashproof grounded devices. Devices with local exhaust Use only in a exhaust booth with integrated air filter. Use in ventilated spray booths only. Ensure that fresh air is supplied to the breathing zone of the operator and exhaust air is removed in his back!

Recirculation of exhaust air is not recommended.

Advice on protection against fire and explosion

Measures to prevent fire :

Extremely flammable. Vapours can form potentially explosive mixtures with air. Reignition possible over considerable distance. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Use non-sparking tools. Flammable vapours can accumulate in head space of closed systems. Only use the material in places where open light, fire and other flammable sources can be kept away. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Usual measures for fire prevention. Wear anti-static footwear and clothing

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Environmental precautions:

Shafts and sewers must be protected from entry of the product. Transfer wash-downs in sealed containers. For restriction of emission on volatile organic compounds (VOC) the solvent vapours should be supplied to an exhaust air purification facility (filter, gas washer, incineration).

Advices on general occupational hygiene :

Use personal protection equipment. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. General health and safety measures The usual precautions when handling chemicals must be observed. Working places should be designed to allow cleaning at any time.

Floors, walls and other surfaces in the hazard area must be cleaned regularly. Clean spray booth and exhaust hood completely with every product change. When using do not eat, drink, smoke, sniff. Thorough

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 7 of 18

skin-cleansing after handling the product. Used working clothes should not be worn outside the work area.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Suitable floor material: Floors should be impervious, resistant to liquids and easy to clean.

Protect against: heat, Cold.

Recommended temperature for storage: +10 - +30°C

Keep away from: Food and feedingstuffs

Keep/Store only in original container.

Hints on joint storage

Do not store together with:

Explosive hazardous substances, Other potentially explosive hazardous substances, flammable solids, Pyrophoric or self-heating substances, Hazardous substances that release flammable gases when in contact with water, Highly oxidising substances, Oxidising substances, Ammonium nitrate and preparations containing ammonium nitrate, Organic peroxides and self-reactive substances, Infectious substances, Radioactive substances

Further information on storage conditions

Technical measures and storage conditions

The applicable provisions of the water and building legislation must be observed. Heating causes rise in pressure with risk of bursting. Keep away from sources of ignition - No smoking. Keep in a cool, well-ventilated place. Keep receptacles tightly sealed. Protect containers against damage. Ensure adequate ventilation of the storage area. Store small packages in a suitable, robust cabinet. Do not store out of doors.

7.3. Specific end use(s)

Lubricants, greases, release products

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-92-2	Butan-2-ol	100	308		TWA (8 h)	WEL
		150	462		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 8 of 18

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2085 mg/m³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m³
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day
74-98-6	propane			
,				
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% n-hexane			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
,				
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
78-92-2	butan-2-ol			
Worker DNEL, long-term		dermal	systemic	405 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	212 mg/m³
Consumer DNEL, long-term		dermal	systemic	203 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	52 mg/m³
Consumer DNEL, long-term		oral	systemic	15 mg/kg bw/day

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 9 of 18

PNEC values

CAS No	Substance	
	Environmental compartment	Value
74-98-6	propane	
78-92-2	butan-2-ol	
	Freshwater	47,1 mg/l
	Marine water	47,1 mg/l
	Freshwater sediment	196,19 mg/kg
	Marine sediment	196,19 mg/kg
	Secondary poisoning	1000 mg/kg
	Micro-organisms in sewage treatment plants (STP)	761 mg/l
	Soil	11,58 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.
Combination filtering device A1P1/A2P2

Thermal hazards

No thermal hazards when using this product.

Environmental exposure controls

Exhaust air may only be led into the open via suitable separators.
Do not allow to enter the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	white
Odour:	characteristic

Test method

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 10 of 18

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	> - 42 °C
Flammability:	The product is: Flammable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	11 vol. %
Flash point:	> - 97 °C
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility: (at 20 °C)	< 50 g/L
Solubility in other solvents miscible with most organic solvents	
Partition coefficient n-octanol/water:	not determined OECD 123
Vapour pressure: (at 20 °C)	< 3000 hPa
Vapour pressure: (at 50 °C)	< 7000 hPa
Density (at 20 °C):	0,645 g/cm ³
Relative vapour density:	> 2,0

9.2. Other information**Information with regard to physical hazard classes**

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solvent content:

56 %

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is chemically stable under recommended conditions of storage, use and temperature.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat, naked flames and other ignition sources.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 11 of 18

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes				
	oral	LD50 5840 mg/kg	rat	ECHA	
	dermal	LD50 > 2800 mg/kg	rat	ECHA	
	inhalation (4 h) vapour	LC50 23,3 mg/l	rat	ECHA	OECD 403
74-98-6	propane				
	inhalation gas	LC50 800000 ppm	Rat	ECHA	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% n-hexane				
	dermal	LD50 2800 - 3100 mg/kg	rat	ECHA	
	inhalation vapour	LC50 25,2 mg/l	rat	ECHA	
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes				
	oral	LD50 > 5840 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 > 2800 mg/kg	Rat	ECHA	OECD 402
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	ECHA	OECD 403
64742-49-0	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 > 5000 mg/kg	Rat	ECHA	OECD 402
78-92-2	butan-2-ol				
	oral	LD50 2054 mg/kg	Rat	ECHA	OECD 423
	dermal	LD50 > 2000 mg/kg	Rat	ECHA	OECD 402

Irritation and corrosivity

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 12 of 18

In case of skin contact:

Irritant

erythema (redness)

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Following inhalation:

slightly irritant but not relevant for classification.

Narcotic effects

On eye contact:

slightly irritant but not relevant for classification.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain any substance that exhibits endocrine disrupting properties towards humans, as no ingredient meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Safety Data Sheet

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes					
	Acute fish toxicity	LC50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD 203
	Acute algae toxicity	ErC50 10-30 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EL50 3 mg/l	48 h	Daphnia magna	ECHA	OECD 202
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	ECHA	
	Algae toxicity	NOEC 6,3 mg/l	4 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC 0,17 mg/l	21 d	Daphnia magna	ECHA	OECD 211
	Acute bacteria toxicity	EC50 26,81 mg/l ()		Tetrahymena pyriformis	ECHA	
106-97-8	butane					
	Acute fish toxicity	LC50 24,11 mg/l	96 h	fish	ECHA	
	Acute algae toxicity	ErC50 7,71 mg/l	96 h	Green algae	ECHA	
	Acute crustacea toxicity	EC50 14,22 mg/l	48 h	Daphnia magna	ECHA	
74-98-6	propane					
	Acute fish toxicity	LC50 49,9 mg/l	96 h	fish	ECHA	
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	algae	ECHA	
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia	ECHA	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% n-hexane					
	Fish toxicity	NOEC 0,17 mg/l	21 d			
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes					
	Acute fish toxicity	LC50 3-10 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD 203
	Acute algae toxicity	ErC50 10-30 mg/l		Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 4,6-10 mg/l	48 h	Daphnia magna	ECHA	OECD 202
	Fish toxicity	NOEC 0,574 mg/l	28 d	Oncorhynchus mykiss	ECHA	
	Algae toxicity	NOEC 10 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC 0,17 mg/l		Daphnia magna	ECHA	OECD 211
64742-49-0	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics					
	Acute fish toxicity	LC50 30 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 46 mg/l	48 h	Daphnia magna	ECHA	OECD 202

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 14 of 18

	Fish toxicity	NOEC mg/l	0,182	28 d	Oncorhynchus mykiss	ECHA	
	Algae toxicity	NOEC	< 1 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC mg/l	0,317	21 d	Daphnia magna	ECHA	
	Acute bacteria toxicity	EC50 mg/l ()	1065		Tetrahymena pyriformis	ECHA	
78-92-2	butan-2-ol						
	Acute fish toxicity	LC50 mg/l	3670	96 h	Pimephales promelas	GESTIS	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			
	OECD 301F	98%	28	
	readily biodegradable			
106-97-8	butane			
	Gas exchange-biodegradation experiment	> 70 %	10	
	readily biodegradable			
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes			
	OECD 301F	98 %	28	
	readily biodegradable			
64742-49-0	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
	OECD 301F	89 %	28	
	readily biodegradable			
78-92-2	butan-2-ol			
	EU Method C.5 / EU Method C.6	86 %	5	ECHA
	readily biodegradable			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,8
74-98-6	propane	2,36
78-92-2	butan-2-ol	0,65

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Ozone depletion potential (ODP):

No data available

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 15 of 18

Photochemical ozone creation potential (POCP):

No data available

Global warming potential (GWP):

No data available

AOX: Product contains no organic halogens.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)**Other applicable information (inland waterways transport)**

Not classified for this transport carrier.

Marine transport (IMDG)

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 16 of 18

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS (Naphtha (Petroleum), hydrotreated, light)
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

ERG Kodex: 10L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 97 %
paints and varnishes:



Safety Data Sheet

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 17 of 18

Additional information

Aerosol directive (75/324/EEC)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Compressed gas

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

**Safety Data Sheet**

According to Regulation (EC) 1907/2006, 2020/878

Release spray TRS

Revision date: 06.06.2024

Product code: 165105

Page 18 of 18

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)